



# SeaLink™ 24 Channel Tension Module

## 24 Channel Data Acquisition

OFFSHORE TECHNOLOGY SOLUTIONS™

Seamap's SeaLink 24 Channel Tension Module is designed to complement the SeaLink 24 Digital Modules and provide cable tension readings along the cable in the SeaLink 3840 Recording System. The SeaLink 24 Channel Tension Cell Modules are designed to be placed in the head, middle and tail of the cable. Tension readings of each tension module are displayed in real time by the SeaLink 3840 Recording System.

The SeaLink 24 Digital Module is the base building block of the system and is powered via a 750 mA DC constant current loop. The 24 channel analog input is capable of sampling at ¼, ½, 1, 2 and 4ms via 24bit delta sigma converters. Digitized data including data from other modules in the array are transmitted to the recording system via Seamap's proven proprietary telemetry system over common electrical twisted pairs. The power, control, data acquisition and systems diagnostics of the modules are performed via the SeaLink workstation on the recording vessel / platform.

The SeaLink 24 Channel Tension Module is enclosed in a 3.0" (76.2mm) OD titanium tube with end-caps. The SeaLink module has a crush depth of 6,925m. The Seamap custom SeaLink 56 pin connector has proven reliable and durable in the harshest environment. All SeaLink Modules have double O-Rings and are Nitrogen filled to ensure mechanical integrity.

The SeaLink 24bit Data Acquisition Systems is based on proven technology and can be configured for many applications including marine seismic data collection.

Custom designs and customizing SeaLink Modules are available upon request. All exposed in-sea metals are titanium.

### Attributes:

- 24 Channels in one Module with Tension Cell
- Selectable Gain
- Selectable Low Cut and High Cut Filters
- Lower Power Consumption
- High Channel Capacity – 480 Channel @ ¼ ms per Array
- Continuous Data Collection
- Sample Rates of ¼, ½, 1, 2 & 4 ms
- Reduced Component Count

### Applications:

- Marine 2D / 3D / 4D Seismic
- High Resolution Seismic
- Ultra High Resolution Seismic
- HR3D Ultra High Resolution Seismic
- Ocean Bottom Cable (OBC)
- Vertical Arrays
- Reservoir Monitoring
- Passive Acoustic Seismic
- Passive Acoustic Monitoring



## Specifications:

SeaLink 24 Channel Tension Module																														
<b>Tension Cell</b>	1 Cell Per Module	Measurement range: 0 to 20,000 lbs. Measurement accurate over operational range: ± 6%; 0 to 1,200 lbs. Operational Temperature range: 15° C to +71° C (60° F to 160° F), Crush depth: 1524 meters <b>Note: Display in lbs. or Kg</b>																												
<b>Number of Seismic Channels</b>	24 Per Module 4 Data Lines <b>(Programmable Per-Application Requirement)</b>	<table border="1"> <thead> <tr> <th>Rate</th> <th>Int.</th> <th>#Chan</th> <th>#Mod</th> </tr> </thead> <tbody> <tr> <td>4000</td> <td>0.25</td> <td>480</td> <td>20</td> </tr> <tr> <td>2000</td> <td>0.50</td> <td>1,008</td> <td>42</td> </tr> <tr> <td>1000</td> <td>1.00</td> <td>2,016</td> <td>84</td> </tr> <tr> <td>500</td> <td>2.00</td> <td>4,128</td> <td>172</td> </tr> <tr> <td>333</td> <td>3.00</td> <td>Custom</td> <td></td> </tr> <tr> <td>250</td> <td>4.00</td> <td>Custom</td> <td></td> </tr> </tbody> </table>	Rate	Int.	#Chan	#Mod	4000	0.25	480	20	2000	0.50	1,008	42	1000	1.00	2,016	84	500	2.00	4,128	172	333	3.00	Custom		250	4.00	Custom	
Rate	Int.	#Chan	#Mod																											
4000	0.25	480	20																											
2000	0.50	1,008	42																											
1000	1.00	2,016	84																											
500	2.00	4,128	172																											
333	3.00	Custom																												
250	4.00	Custom																												
<b>Non-Seismic Channels Allocated</b>	NAD Channels	Internal Pressure Internal Temperature Voltage Measurements Current Measurements																												
<b>Analog/Digital Converter</b>	24bit Delta Sigma Type																													
<b>Dynamic Range</b>	> 112 dB (5-206 Hz)	Based on 2ms Sample Rate																												
<b>Distortion</b>	THD < 0.003%	Based on 2ms Sample Rate																												
<b>Lower Power Consumption</b>	Less than 3.3 watts per module (86 mwatts per-channel)																													
<b>Preamplifier Type</b>	Voltage Mode Differential Input	<b>Selectable Gain +1.0% accuracy: 0 to 36 dB Increments in 6dB steps</b>																												
<b>Low Cut Filter</b>	Analog	5Hz 6db/Oct (Hydrophone Cap + Input Z)																												
<b>Low Cut Filter</b>	Digital Infinite Impulse (IIR) Filter	Selectable Settings: .1 to 10Hz in 1 Hz Increments 6db/Oct																												
<b>High Cut Filter</b>	Digital Linear Phase																													
<b>Selectable Sample Rates</b>	0.25 mS 0.5 mS 1.0 mS 2.0 mS 4.0 mS	-3 dB Corner Frequency: 1652Hz -3 dB Corner Frequency: 824Hz -3 dB Corner Frequency: 412Hz -3 dB Corner Frequency: 206Hz Custom																												
<b>Functional Testing</b>	Source: Internal Test Oscillator, Frequency: 31.25 Hz, Sine Wave																													
<b>Tests</b>	DC Offset, RMS Noise, Channel Gain Accuracy, Impulse Response Hydrophone Leakage, Harmonic Distortion, Crosstalk																													
<b>SeaLink 24 Digital Module Physical Dimensions</b>	Length: 14.43" (366.52 mm) Overall: 19.59" (497.58 mm) OD: 3.0" (76.22 mm)	Weight in air: 6.18 lbs (2.803 Kg) Weight in water: 3.15 lbs (1.428 Kg)																												



seamap.com

### Seamap (U.K.) Ltd.

Unit 34, The Maltings, Charlton Estate  
Shepton Mallet, Somerset, BA4 5QE, U.K.  
Tel: +44 [0] 1749 342223  
Fax: +44 [0] 1749 347588  
email: sales@seamap.com

### Seamap Inc.

P.O. Box 1175, Huntsville, TX 77342  
United States of America  
Tel: +1 936 291 2277  
Fax: +1 936 295 1922

### Seamap Pte Ltd.

51 Changi North Crescent  
Singapore 499626  
Tel: +65 6545 1054  
Fax: +65 6545 0585

Seamap (U.K.) Ltd., Seamap Inc., Seamap Pte Ltd (hereafter Seamap) reserves the right to make any changes without notice to any of the products herein at its discretion. Seamap does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights nor the rights of any others. All product names referenced herein are trademarks of their respective companies. Copyright © 2002-2018 by Seamap 11-00-1028-A

